



Technical Description:
 1.The dimensions marked in the figure are the centerline dimensions, measured in millimeters;
 2.The installation height of the fence is 2130 (excluding the foundation), and the center distance of the columns is 2540 ± 5;
 3.The fence is composed of directly buried columns (including top cover), connectors, mesh and other components;
 4.The column adopts "I-shaped" straight seam welded pipe, made of continuous hot-dip galvanized steel plate, Q235 material, with a galvanizing amount of ≥ 120g/m² (double-sided);
 5.The cross-sectional size of the column is 54.4 x 100 x 1.5, with a height of 2050;
 6.The mesh is made of high-strength cold drawn hot-dip galvanized steel wire resistance welding, with steel wire material Q195, steel wire tensile strength ≥ 450MPa, steel wire diameter of Ø6 (horizontal wire)+Ø5 (vertical wire)+Ø6 (horizontal wire)+, and galvanizing amount ≥ 120g/m²;
 7.The height of the mesh is 2030, the width is 2500, the grid is 50 (vertical wires) x 200 (horizontal wires), and the reinforcement groove is 50 (vertical wires) x 50 (horizontal wires);
 8.The surface of the columns and mesh is coated with high adhesion thermosetting polyester powder electrostatic coating, with a coating thickness of ≥ 100 μm, coating adhesion ≥ 0 level, coating gloss 80-95°, photo aging ≥ 0 level, and weather resistance ≥ 5;
 9.The fence foundation is made of ≥ 28MPa concrete cast-in-place (can be prefabricated), with 150 x 150 x 350 column embedding holes reserved. After the columns are embedded, they are fixed by secondary pouring at a depth of 300;

COLLIAND		Project Name:	Project No.
		Building Name:	Drawing Phase
Drawn by	Verified by	PSN&GP-2130 Fence construction drawing	Drawing No.
Designed by	Examined by		Scale
Checked by	Project Principal		Version
			Date

Former outline drawing Number
 Outline drawing Number
 Signature
 Ddte